

R302301 Patch Cord Cat.6, U/UTP, 4P, PVC/LSZH, gray, RJ45/u-RJ45/u, 2.0 m

010.2076

**Description**

Cable identification: U/UTP.

Outer jacket: PVC or LSZH

Conductor diameter copper strand: AWG26/7.

Screened in pairs: no.

Overall screen: no.

Outer diameter: max. 6.0 mm.

Weight

78.000G

Technical Data

Standardisation	Compliant with Cat.6, Class E (250 MHz) requirements: ISO/IEC 11801 ed. 2.2 Compliant with Cat.6 component standards IEC 60603-7-4 and 60603-7-5
Connector type (A)	RJ45
Category connector (A)	Cat.6
Shielding - connector (A)	No
Connector type (B)	RJ45
Category connector (B)	Cat. 6
Shielding - connector (B)	No
Category	Cat.6
Cable class	Patch Cord
Cu cable shielding	U/UTP
Number of fibers / conductors	8
Stranding	4x2
Cable overall diameter	max. 6.0 mm
Conductor type	stranded conductor
Fiber / conductor diameter	AWG 26/7
Length (meter)	2.0
Cable jacket material	PVC or LSZH
Cable jacket characteristics	cable, metal-free
Color	cable, gray (RAL 7035)
Dispatch weight	78.000
Unit of dispatch weight	G